

CAS3047

1WAN 4 LAN Broadband Cable/DSL Router

Features

- Superb performance with high throughput up to 80Mbps between Internet and LAN.
- Web UI management.
- Web Wizard simplifies user setup procedures.
- Windows Wizard auto-detects ISP service for 1st time setup.
- Support PPPoE.
- Support PPTP client.
- Support VPN. (PPTP, IP- Sec pass thru)
- Support Auto MDI/MDIX for both LAN/WAN port.
- Rich Internet applications are supported such as MSN, StarCraft, AOE, Battle.net multi-user, Crazy Arcade, NetMeeting, ICQ, VoIP phone, mIRC, Web browser, FTP, Telnet, E-Mail, News, Ping, PC-AnyWhere...
- DHCP server allocates up to 253 client IP addresses.
- Allow to set 32 Static DHCP.
- Proxy DNS.
- Dynamic DNS. (DDNS)
- Allow to set 24 Virtual Server.
- DMZ host & Multi-DMZ.
- Allow to set 24 Packet Filters.
- Static routing.
- Super manager.
- Allow firmware upgrade through network.
- Support Windows 95/98/ME/NT/2000/XP, Unix, and Mac.
- Natural firewall keeps hackers out.
- Load/Save device settings from/to a PC file



SPECIFICATIONS

Standards

IEEE 802.3 10Base-T Ethernet
IEEE 802.3u 100Base-TX Fast Ethernet
IEEE 802.3x Flow Control

Ports

WAN: One 10/100Mbps RJ-45 port for Cable/DSL Modem
LAN: Four 10/100Mbps switched ports

Cabling type UTP Category 5 or better (100Base-TX)

Protocols Supported IP, NAT, ARP, ICMP, DHCP client/server, PPPoE, PPP, PAP, CHAP, NTP, HTTP

Management Web-Based configuration and management, or GUI Setup program for Windows 98/ME/NT/2000/XP

LED indicators

Power Green for ON
Status Red for error
Internet Green for 100M/10M (flashing for activity)
Local (1-4) Green for 100M/10M (flashing for activity)

Input power DC 9V 700mA

Physical Dimension 134 x 90 x 29 mm³ (W x D x H)

Weight 175 g

Agency and Regulatory FCC part 15 Class B, CE, VCCI, BSMI

Operating Temperature 0°C to 50°C

Operating Humidity 0-90% non-condensing

